

Die Cast Machinery, LLC Inventory number: DCM-2858

Used Mokon Model: 18 KW Single Zone Portable Combination Heated and Refrigerated Water Chiller Heat Temperature Control Unit

Status:	Sold
Manufacturer:	Mokon
Size:	18 KW
Inventory Number:	DCM-2858

Mokon - 18 KW Single Zone Portable Combination Heated and Refrigerated Water Chiller Heat Temperature Control Unit, Controls

[View this machine online: DCM-2858](#)



Specifications

	U.S. Standard	Metric
Zone Motor	3/4 hp	0.56 kw
Compressor Motor	3 hp	2.24 kw
Supply Motor	3/4 hp	0.56 kw
Refrigerant	R-22	R-22
Temperature Range - Open Circuit	50 to 180-Degree Fahrenheit	10 to 82.22-Degree Celsius
Temperature Range - Closed Circuit	50 to 250-Degree Fahrenheit	10 to 121.11-Degree Celsius

Features & Accessories:

- Three (3) Ton Water Cooled Scroll Chiller
- Eurotherm Model 2404 Microprocessor Controller
- RS485 Serial Communication with SPI Protocol
- Gauges: Process Pump, Tank Temp, Low Refrig., High Refrig.
- Rear Inputs: From/To Process, Supply/Drain Water
- Electrical Rating: 230 Volt, 3 Phase, 60 Hertz

Terms of Sale:

Price: [sold](#)

Shipping Terms: Ex-works

Questions? Call (847) 360-9170 and mention DCM-2858.

Photos - DCM-2858

Click any photo to open it full size on our website.



[Photo 1 of DCM-2858 - view online](#)



[Photo 2 of DCM-2858 - view online](#)



[Photo 3 of DCM-2858 - view online](#)



[Photo 4 of DCM-2858 - view online](#)



[Photo 5 of DCM-2858 - view online](#)



[Photo 6 of DCM-2858 - view online](#)

Photos - DCM-2858 (continued)

Click any photo to open it full size on our website.



[Photo 7 of DCM-2858 - view online](#)



[Photo 8 of DCM-2858 - view online](#)

Description:

Used, Mokon Model 18 KW Single Zone Portable Combination Heated and Refrigerated Water Chiller Heat Temperature Control Unit For_Sale, Features Include: Three (3) Ton Water Cooled Scroll Chiller, Eurotherm Model 2404 Microprocessor Controller, RS485 Serial Communication with SPI Protocol, Gauges: Process Pump, Tank Temp, Low Refrig., High Refrig., Rear Inputs: From/To Process, Supply/Drain Water, Electrical Rating: 230 Volt, 3 Phase, 60 Hertz, controls, second Hand, DCM-2858

PURCHASER'S (Buyer's) RESPONSIBILITY AND INDEMNITY: Used machines, equipment or any part thereof, may not incorporate approved activating mechanisms, operator safety devices or safety guards as required by OSHA or otherwise. It shall be a Purchaser's (Buyer's) responsibility to ensure that any and all merchandise or equipment purchased from Die Cast Machinery, LLC or its affiliates is installed and operated in a proper and safe manner. Purchaser (Buyer) also acknowledges that it may have to install or change guards, safeties, warnings or other components to ensure that the merchandise or machines purchased will conform to all laws, codes, regulations, ordinances, statutes, insurance requirements and industry standards. Purchaser agrees to defend, indemnify and hold harmless Die Cast Machinery, LLC from and against all suits, claims, costs, damages and expenses, including, but not limited to, reasonable attorneys' fees, arising out of, or in connection with, the transportation, purchase, ownership, or use of the merchandise or equipment sold hereunder. Information has been obtained from sources deemed reliable, buyers should avail themselves of the opportunity to inspect the items before purchase.